


Grad. Alc. 9° G.L. / % vol. Alc.
Grad. Alc. 9,5° G.L. / % vol. Alc.
Grad. Alc. 10° G.L. / % vol. Alc.
Grad. Alc. 10,5° G.L. / % vol. Alc.
Grad. Alc. 11° G.L. / % vol. Alc.
Grad. Alc. 11,5° G.L. / % vol. Alc.
Grad. Alc. 12° G.L. / % vol. Alc.
Grad. Alc. 12,5° G.L. / % vol. Alc.
Grad. Alc. 13° G.L. / % vol. Alc.
Grad. Alc. 13,5° G.L. / % vol. Alc.
Grad. Alc. 14° G.L. / % vol. Alc.



COLOCAR VARIABLE SEGÚN OC

	(*)	GA	(*)
5	A	11	N
5.5	B	11.5	O
6	C	12	P
6.5	D	12.5	Q
7	E	13	R
7.5	F	13.5	S
8	G	14	T
8.5	H	14.5	U
9	J	15	V
9.5	K	15.5	W
10	L	16	X
10.5	M		

Medidas (ancho x alto)	60 x 100 mm.
Papel	Coated 80 Premium/ AP903 / PET30
Barniz	Acuoso Mate
Impresión y Pegado	Digital / Offset rot / Flexo/Autoadhesivo
Sentido de salida	AISA 3 (Molina) / AISA 4 (Isla de Maipo)
Diámetro rollo	350mm +/- 10mm (aplicando redondeo de cantidades)
Paso etiquetas/contras	entre 3 y 4,5 mm
	NUNCA inferior a 3mm

Colores		
	Negro	Pantone 354 C

Recursos