

Archivo preparado por: **Camila Orozco** / mail: caorozc@vspt.cl

PARA USO INTERNO

TIV: VP0CB01301

TARAPACA
establecida en 1874
CHARDONNAY • 20XX

Appearance: Pale yellow with greenish hues. **Nose:** Notes of bananas and peaches along hints of toast. **Mouth:** Smooth, balanced and refreshing. **Pairing:** Shellfish, indian food, pasta dishes and salads. **Serve at:** 10 - 12 °C.

DRINKING ALCOHOL CAUSES LIVER DISEASE
THERE IS A DIRECT LINK BETWEEN ALCOHOL AND FATAL CANCERS
Visit www.askaboutalcohol.ie

Scan for ingredients and nutritional information

Imported by: BWG Wines & Spirits.
BWG House, Greenhills Road,
Tallaght, Dublin 24, Ireland.

100ml: E= 314 kJ/ 75 kcal

DEJAR ESPACIO EN BLANCO para imprimir N° de lote en planta

magnificación 80% truncada alto (aleatorio) 29,83 x 18mm

EAN-13 780434060000-4

75 cl e XX,XX% vol

Contains Sulphites WINE OF CHILE

Produced and bottled by
Viña San Pedro Tarapacá S.A.,
Av. Vitacura 2670, piso 16,
Las Condes, Santiago - Chile.
Envasado en Chile
www.TARAPACA.CL

Grados	Gramos	Volumen (vol)
6°	36 grams	11% vol
6,5°	38 grams	11,5% vol
7°	41 grams	12% vol
7,5°	44 grams	12,5% vol
8°	47 grams	13% vol
8,5°	50 grams	13,5% vol
9°	53 grams	14% vol
9,5°	56 grams	
10°	59 grams	
10,5°	62 grams	
11°	65 grams	
11,5°	68 grams	
12°	71 grams	
12,5°	74 grams	
13°	77 grams	
13,5°	80 grams	
14°	83 grams	
14,5°	86 grams	
15°	89 grams	

colocar según grado alc (botella 750cc)

COLOCAR VARIABLE SEGÚN OC

GA (*)	GA+ COSECHA (a)					
11	N0	N1	N2	N3	N4	N5
11.5	O0	O1	O2	O3	O4	O5
12	P0	P1	P2	P3	P4	P5
12.5	Q0	Q1	Q2	Q3	Q4	Q5
13	R0	R1	R2	R3	R4	R5
13.5	S0	S1	S2	S3	S4	S5
14	T0	T1	T2	T3	T4	T5
14.5	U0	U1	U2	U3	U4	U5
15	V0	V1	V2	V3	V4	V5
15.5	W0	W1	W2	W3	W4	W5
16	X0	X1	X2	X3	X4	X5



Medidas (ancho x alto)	70 x 100 mm
Papel	Fasson Cuvee Estate #100_S0300_PET 30 (<i>papel principal</i>) ENVI- PCW100 WSA-FSC - RS30 - PET 30 PCR - (WL72E) Eng (<i>papel Backup</i>)
Barniz	UV Mate
Impresión y Pegado	Xeikon / Autoadhesiva
Sentido de salida	AISA 3 (Molina) / AISA 4 (Isla de Maipo)
Diámetro rollo	350mm +/- 10mm (aplicando redondeo de cantidades)
Paso etiquetas/contras	entre 3 y 4,5 mm NUNCA inferior a 3mm

Colores

