

72 mm

98 mm

EACH BOTTLE YOU ENJOY SUPPORTS REFORESTATION



MADE WITH ORGANIC GRAPES

SCX PRODUCT

CO₂ neutral

FUNDACIÓN REFORESTEMOS

CERTIFIED sustainable

RECYCLING INSTRUCTIONS

BOTTLE

LABELS

SCREW CAP

GLASS

PAPER

ALUMINUM

RECYCLE

LEAVE ON BOTTLE

RECYCLE

GOVERNMENT WARNING: (1) ACCORDING TO THE SURGEON GENERAL, WOMEN SHOULD NOT DRINK ALCOHOLIC BEVERAGES DURING PREGNANCY BECAUSE OF THE RISK OF BIRTH DEFECTS. (2) CONSUMPTION OF ALCOHOLIC BEVERAGES IMPAIRS YOUR ABILITY TO DRIVE A CAR OR OPERATE MACHINERY, AND MAY CAUSE HEALTH PROBLEMS.

Imported by:

Imported by Park Street Imports, Miami, FL.

PRODUCED AND BOTTLED BY Viña San Pedro Tarapacá S.A.

Av. Vitacura 2670, piso 16, Las Condes, Santiago - Chile.

Certified Organic by Ecocert.

ENVASADO EN CHILE

www.sanpedro.cl

MADE WITH ORGANIC GRAPES

SAUVIGNON BLANC

B-liv is a wine brand committed to sustainability, offering quality wines that are as gentle on the environment as they are delightful to the palate. Our wines are crafted from organic grapes and packaged using recycled and recyclable materials. We're proud to be carbon neutral and to donate 1% of our profits to the planet.

This Sauvignon Blanc is fresh, with intense fruity aromas of citrus and tropical fruits. On the palate, it has vibrant acidity and a long, balanced finish.

CA CRV

Alc. XX.X% by Vol. 750 ML

PRODUCT OF CHILE WINE OF CHILE

CONTAINS SULFITES WHITE WINE

ME 15c 1A 5c

DEJAR ESPACIO EN BLANCO para imprimir N° de lote en planta

magnificación 80% truncada alto (aleatorio) 29,83 x 18mm

UPC 8 10098 40027 5

5mm

*N2H

12% by Vol.

12,5% by Vol.

13% by Vol.

13,5% by Vol.

14% by Vol.

14,5% by Vol.

15% by Vol.

COLOCAR VARIABLE SEGÚN OC

GA	(*)
11	N
11.5	O
12	P
12.5	Q
13	R
13.5	S
14	T
14.5	U
15	V
15.5	W
16	X

Medidas (ancho x alto)	72 x 98 mm	Colores	 CMYK	 P 2299 U	 P 2035 U
Papel	WOODSTOCK BETULLA FSC / SH9020 / PET 30 (Fedrigoni)				
Barniz	UV Mate				
Impresión y Pegado	Offset Rot. /Flexo/Autoadhesiva				
Sentido de salida	AISA 3 (Molina) / AISA 4 (Isla de Maipo)				
Diámetro rollo	350mm +/- 10mm (aplicando redondeo de cantidades)				
Paso etiquetas/contras	entre 3 y 4,5 mm				
	NUNCA inferior a 3mm				