

Archivo preparado por: **Fabiola Azúa** / fazua@vspt.cl

72 mm

98 mm

EACH BOTTLE YOU ENJOY SUPPORTS REFORESTATION



MADE WITH ORGANIC GRAPES

PRODUCT





CERTIFIED

sustainable

CL

RECYCLING INSTRUCTIONS

BOTTLE

GLASS

RECYCLE

LABELS

PAPER

LEAVE ON BOTTLE

CORK

ORGANIC

SEPARATE AND COMPOST

GOVERNMENT WARNING: (1) ACCORDING TO THE SURGEON GENERAL, WOMEN SHOULD NOT DRINK ALCOHOLIC BEVERAGES DURING PREGNANCY BECAUSE OF THE RISK OF BIRTH DEFECTS. (2) CONSUMPTION OF ALCOHOLIC BEVERAGES IMPAIRS YOUR ABILITY TO DRIVE A CAR OR OPERATE MACHINERY, AND MAY CAUSE HEALTH PROBLEMS.

Imported by:

Imported by Park Street Imports, Miami, FL.

PRODUCED AND BOTTLED BY Viña San Pedro Tarapacá S.A.

Av. Vitacura 2670, piso 16, Las Condes, Santiago - Chile.

Certified Organic by Ecocert.

ENVASADO EN CHILE

www.sanpedro.cl

MADE WITH ORGANIC GRAPES

RED BLEND

B-liv is a wine brand committed to sustainability, offering quality wines that are as gentle on the environment as they are delightful to the palate. Our wines are crafted from organic grapes and packaged using recycled and recyclable materials. We're proud to be carbon neutral and to donate 1% of our profits to the planet.

This Red Wine Blend has a deep ruby-red color and intense fruity aromas. The palate is medium-bodied and flavorful, with balanced acidity and smooth tannins.

CA CRV

5mm

Alc. XX.X% by Vol. 750 ML

PRODUCT OF CHILE

WINE OF CHILE

CONTAINS SULFITES

RED WINE

ME 15g / 14.5g

DEJAR ESPACIO EN BLANCO

para imprimir N° de lote en planta

magnificación 80%

truncada alto (aleatorio)

29,83 x 18mm

UPC

8 10098 40028 2

HQO*

COLOCAR VARIABLE SEGÚN OC

GA	(*)
11	N
11.5	O
12	P
12.5	Q
13	R
13.5	S
14	T
14.5	U
15	V
15.5	W
16	X

Medidas (ancho x alto)	72 x 98 mm	Colores			
Papel	WOODSTOCK BETULLA FSC / SH9020 / PET 30 (Fedrigoni)		CMYK	P 2355 U	P 2035 U
Barniz	UV Mate				
Impresión y Pegado	Offset Rot. /Flexo/Autoadhesiva				
Sentido de salida	AISA 3 (Molina) / AISA 4 (Isla de Maipo)				
Diámetro rollo	350mm +/- 10mm (aplicando redondeo de cantidades)				
Paso etiquetas/contras	entre 3 y 4,5 mm				
	NUNCA inferior a 3mm				